

DECLARATION OF PERFORMANCE Date of issue: 4/10/2017 Replaces: No --- - CPR --/--- - yyyy/# of: dd/mm/yyyy No. 0761-CPR-16/0310-2017/4 1 PROMASEAL®-A spray Unique identification of the product-type: Type and batch numbers: as given on the packaging of the product Intended uses as given in the ETA-16/0310: 3.1 - PROMASEAL®-A spray is a one-component, sprayable, elastic fire stopping acrylic for linear gaps/joints with different backfilling materials in walls and floors. 3.2 - The product is intended for: - use at internal conditions with humidity < 85% RH, excluding temperatures below 0°C, without exposure to rain and UV (TR 024:2009, type Z2) - use at internal conditions with humidity ≥ 85%, excluding temperatures below 0°C, without exposure to rain and UV (TR 024:2009, type Z1); - use at temperatures below 0°C, but no exposure to rain or UV (TR 024:2009, type Y2); - use at temperatures below 0°C, with exposure to UV but no exposure to rain (TR 024:2009, type Y1); Name and contact address of the manufacturer: Promat International NV Bormstraat 24 B-2380 Tisselt Belgium Plant:12 www.promat-international.com Authorised representative: not applicable. System or systems of Assessment and Verification of Constancy of Performance (AVCP): see table under section The construction product is not covered by a harmonised standard (hEN). The declaration of performance concerns a construction product for which a European Technical Assessment has been issued. The Österreichische Institut für Bautechnik (OIB, Austria) has issued an ETA for this product with no. ETA-16/0310 based on ETAG 026-1 and ETAG 026-3. Notified product certification body: No. 0761 (MPA Braunschweig) Certificate of Constancy of Performance 0761 - CPR - 0577 **Declared performance Essential characteristics** AVCP systems Performance Harmonised technical specification BR1: Mechanical resistance and stability. BR2: Safety in the case of fire: Reaction to fire: This characteristic depends on the tested Resistance to fire: assembly. A fire resistant construction, in which the product was used, has been tested and ETA 16/0310 the performance class has been established in a classification document in accordance with the applicable part of EN 13501. BR3: Hygiene, Health and the Environment: Air permeability: NPD (No Performance Declared) NPD (No Performance Declared) Water impermeability: Release of dangerous substances: Declaration (filed with the Technical ETA 16/0310 Approval Body) BR4: Safety and accessibility in use: Mechanical resistance and stability: NPD (No Performance Declared) NPD (No Performance Declared) ETA 16/0310 Resistance to impact and movement:



id dollbo

Adhesion:		NPD (No Performance Declared)	
BR5: Protection against noise:			
Airborne sound insulation:		NPD (No Performance Declared)	ETA 16/0310
BR6: Energy Economy and Heat Retention:			
Thermal conductivity:	-	NPD (No Performance Declared)	
Water vapour permeability (transmission	-	NPD (No Performance Declared)	ETA 16/0310
coefficient):			
Durability:			
Basic durability assessment:		In accordance with the declared use, class	
		Z2, Z1, Y2, Y1 according EOTA TR024	ETA 16/0310
		and in conformity with ETAG 026-3.	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

The reader of this document is invited to verify on the website www.promat-ce.eu the relevant version..

The Safety Data Sheet (SDS) 1907/2006/EG for PROMASEAL®-A spray is available on request.

Signed for and on behalf of the manufacturer by:

Name: Bettina Rothböck

Function: Product Manager Fire Stopping & Intumescent

Seals

Linz, 4/10/2017 Signature: